



**9418 Non-Paired - Audio, Control and Instrumentation Cable**

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

**Description:**

18 AWG stranded (19x30) tinned copper conductors, conductors cabled, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Conductors	4
Total Number of Conductors	4
AWG	18
Stranding	19x30
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material	S-R PVC - Semi-Rigid Polyvinyl Chloride
Nom. Insulation Wall Thickness	.010 in.

**OVERALL CABLING:**

Overall Cabling Lay Length	2.0 in.
----------------------------	---------

Overall Cabling Color Code Chart :

Number	Color	Number	Color
1	Red	3	Black
2	Green	4	White

**OUTER SHIELD:**

Outer Shield Material Trade Name	Beldfoil® (Z-Fold®)
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %
Outer Shield Drain Wire AWG	20
Outer Shield Drain Wire Stranding	Stranded
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.035 in.



**9418 Non-Paired - Audio, Control and Instrumentation Cable**

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.245 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-20°C To +80°C
UL Temperature Rating	80°C (UL AWM Style 2464)
Bulk Cable Weight	48.3 lbs/1000 ft.
Max. Recommended Pulling Tension	100 lbs.
Min. Bend Radius (Install)	2.5 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CMG
CEC/C(UL) Specification	CMG
AWM Specification	UL Style 2464 (300 V 80°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

**FLAME TEST:**

UL Flame Test	UL1685 FT4 Loading
C(UL) Flame Test	FT4

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
Plenum Number	89418 or 82418

**ELECTRICAL CHARACTERISTICS:**

Nom. Capacitance Conductor to Conductor @ 1 KHz	70 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	120 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	6.5 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	8.5 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (UL AWM Style 2464)
Max. Recommended Current	5 Amps per conductor @ 25°C

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9418 060100	4 #18 PVC FS FRPVC	100	5.3	CHROME	
9418 0601000	4 #18 PVC FS FRPVC	1000	49	CHROME	C



**9418 Non-Paired - Audio, Control and Instrumentation Cable**

9418 06010000	4 #18 PVC FS FRPVC	10000	520	CHROME	C Y
9418 060500	4 #18 PVC FS FRPVC	500	24.5	CHROME	C
9418 060U1000	4 #18 PVC FS FRPVC	U1000	47	CHROME	
9418 060U500	4 #18 PVC FS FRPVC	U500	25	CHROME	

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Revision Number: 2      Revision Date: 05-25-2005

© 2005 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.